



# SAFETY JOGGER

## INDUSTRIAL



Medium

## BESTFIT S1 P

### Safety boot with heel tab and elasticated sides

The Safety Jogger BESTFIT safety shoe combines advanced features like SRC slip resistance, antistatic properties, and puncture-resistant steel midsole. It offers unmatched comfort with its breathable leather upper and removable footbed, ideal for demanding industries.

|               |                                                                     |
|---------------|---------------------------------------------------------------------|
| Upper         | Nappa Action Leather                                                |
| Lining        | Cambrella                                                           |
| Footbed       | SJ foam footbed                                                     |
| Midsole       | Steel                                                               |
| Outsole       | PU/PU                                                               |
| Toecap        | Steel                                                               |
| Category      | S1 P / SRC                                                          |
| Size range    | EU 36-48 / UK 3.5-13.0 / US 4.0-13.5<br>JPN 22.5-31.5 / KOR 235-315 |
| Sample weight | 0.678 kg                                                            |
| Norms         | ASTM F2413:2018<br>EN ISO 20345:2011                                |



DBN



BLK




#### Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



#### Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



#### Oil & fuel resistant

The outsole is resistant against oil and fuel.



#### Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



#### Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



#### S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.

SAFETY  
JOGGER  
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com

Industries:

Automotive, Catering, Chemical, Cleaning, Construction, Food & beverages, Logistics, Mining, Oil & Gas, Industry

Environments:

Dry environment, Muddy environment, Uneven surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|         | Description                                                      | Measure unit | Result      | EN ISO 20345 |
|---------|------------------------------------------------------------------|--------------|-------------|--------------|
| Upper   | <b>Nappa Action Leather</b>                                      |              |             |              |
|         | Upper: permeability to water vapor                               | mg/cm²/h     | 1.7         | ≥ 0.8        |
|         | Upper: water vapor coefficient                                   | mg/cm²       | 18.5        | ≥ 15         |
| Lining  | <b>Cambrella</b>                                                 |              |             |              |
|         | Lining: permeability to water vapor                              | mg/cm²/h     | 33.5        | ≥ 2          |
|         | Lining: water vapor coefficient                                  | mg/cm²       | 269         | ≥ 20         |
| Footbed | <b>SJ foam footbed</b>                                           |              |             |              |
|         | Footbed: abrasion resistance (dry/wet) (cycles)                  | cycles       | 25600/12800 | 25600/12800  |
| Outsole | <b>PU/PU</b>                                                     |              |             |              |
|         | Outsole abrasion resistance (volume loss)                        | mm³          | 24.3        | ≤ 150        |
|         | Outsole slip resistance SRA: heel                                | friction     | 0.34        | ≥ 0.28       |
|         | Outsole slip resistance SRA: flat                                | friction     | 0.33        | ≥ 0.32       |
|         | Outsole slip resistance SRB: heel                                | friction     | 0.16        | ≥ 0.13       |
|         | Outsole slip resistance SRB: flat                                | friction     | 0.19        | ≥ 0.18       |
|         | Antistatic value                                                 | MegaOhm      | 223         | 0.1 - 1000   |
|         | ESD value                                                        | MegaOhm      | N/A         | 0.1 - 100    |
|         | Heel energy absorption                                           | J            | 33          | ≥ 20         |
| Toecap  | <b>Steel</b>                                                     |              |             |              |
|         | Impact resistance toecap (clearance after impact 100J)           | mm           | N/A         | N/A          |
|         | Compression resistance toecap (clearance after compression 10kN) | mm           | N/A         | N/A          |
|         | Impact resistance toecap (clearance after impact 200J)           | mm           | 17.5        | ≥ 14         |
|         | Compression resistance toecap (clearance after compression 15kN) | mm           | 21.0        | ≥ 14         |

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com